CLAIMS

- 1. A composite material comprising a plurality of cores of ultra-hard material, or the components for making an ultra-hard material, dispersed in a matrix, the matrix comprising the components for making an ultra-hard material of a grade different to that of the cores, and a suitable binder.
- 2. A composite material according to claim 1, wherein the ultra-hard material is polycrystalline diamond (PCD) or polycrystalline cubic boron nitride (PcBN).
- 3. A composite material according to claim 2, wherein the cores are provided as individual particles or in the form of granules.
- 4. A composite material according to any one of the preceding claims, wherein the cores are made from a fine-grained PCD grade material and the matrix of a coarser PCD grade material than that of the cores.
- A composite material according to any one of claims 1 to 3, wherein the cores are made from a coarser PCD grade material and the matrix of a fine-grained PCD grade material.
- A composite material according to claim 4 or claim 5, wherein the fine-grained PCD grade material has grains having a grain size in the range of about 0.1 to about 20 microns.
- 7. A composite material according to any one of claims 4 to 6, wherein the coarser PCD grade material has grains having a grain size in the range of about 10 to about 100 microns.
- 8. A composite material according to any one of claims 1 to 5, wherein the cores and matrix are made from the same type of ultrahard

- material, and the particle size of the cores differs from that of the matrix by between about 5 and about 70 microns.
- A composite material according to any one of claims 1 to 3, wherein 9. the cores and the matrix are made from the same ultrahard material, but with different binder phases.
- A composite material according to any one of claims 1 to 3, wherein 10. the cores are formed of PCD and the matrix of PcBN type material.
- A composite material according to any one of claims 1 to 3, wherein 11. the cores are formed from PcBN type material.
- A composite material according to any one of claims 1 to 3, wherein 12. the cores and matrix are made from mixtures of two types of ultrahard materials, those mixtures being substantially different from each other.
- A method of producing a composite material as defined in any one 13. of claims 1 to 12, which includes the steps of:
 - providing a plurality of cores of an ultra-hard material or the (i) components for making an ultra-hard material;
 - providing the components for making an ultra-hard material (ii) of a different grade to that of the cores and a suitable binder; and
 - consolidating the cores, components and binder to produce (iii) a composite material.
- A method of producing a tool component including the steps of: 14.
 - providing a substrate; (i)

- (ii) providing a composite material as defined in any one of claims 1 to 12;
- (iii) placing a layer of the composite material on a surface of the substrate to produce an unbonded component; and
- (iv) subjecting the unbonded component to conditions of elevated temperature and pressure suitable to produce an ultra-hard material.
- 15. A method according to claim 13 or claim 14, wherein the cores are provided as granules coated with the components for making an ultra-hard material and the binder.
- 16. A method according to claim 13 or claim 14, wherein the cores are provided as granules, and the granules are mixed with the components for making an ultra-hard material and the binder.